



TRIVA T-aAY

TECHNICAL INFORMATION



Type

- foldable, trifocal, toric, posterior chamber IOL
- one-piece with C-loop haptics
- available in preloaded Safeloader autoloading container

Material

- hydrophilic acrylic with UV absorber
- water content 26 %
- blue-light protection
- Abbe number 56
- refractive index 1.46

Specifics

- aspheric anterior surface (aberration-free) with central diffractive zone
- toric aspheric posterior surface, omnidirectional aberration-free
- intermediate addition + 1.75 D, near addition +3.5 D (at IOL plane)
- posterior surface with 360° lens epithelial cell barrier

Diopter Range

SE in 0.5 D steps 10.0 to 30.0 D **SL**

Cylinder in 0.5 D steps 1.0 to 6.0 D

Cylinder Axis

The two thin diametrically opposed lines in the periphery of the optic indicate the axis of the plus-cylinder

Est. A-const

For a complete list of recommended constants, please visit humanoptics.com



SL = Safeloader

©0044

 HumanOptics Holding AG

Spardorfer Str. 150 · 91054 Erlangen · Germany · Phone +49 (0) 9131 50 66 5-0 · Fax +49 (0) 9131 50 66 5-90
mail@humanoptics.com · www.humanoptics.com